

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1 Claim 1 (original): A system for an internal combustion engine (10) designed to be operated with a fuel  
2 mixed with a lubricant characterized in that it comprises:

- 3 • a detector (16) arranged to detect the presence of a specific additive in the lubricant  
4 mixed fuel,
- 5 • an electronic module (24) arranged to compare the detected presence of an additive with  
6 a given threshold value and designed so that; if the lubricant has not been mixed in the  
7 fuel or is mixed into the fuel, in an amount that is lower than an, via the additive against  
8 the threshold value correlated, amount, by means of an indicator (30) indicate a lack of  
9 lubricant in the fuel and/or with a connection (26) to an ignition system or an injection  
10 system (11) for the engine (10) prevent or change the operation of the internal  
11 combustion engine if such lack of lubricant is at hand in the fuel.

1 Claim 2 (original): A system according to claim 1, characterized in that said threshold value is adjustable  
2 for a correlation against the type of additive and the limits for a mixing ratio between fuel, lubricant and  
3 additive.

1 Claim 3 (original): a system according to claim 1 or 2, characterized in that said electronic module (24)  
2 via said connection (26) to the ignition system (11) of the internal combustion engine (10), is arranged  
3 to limit the speed (RPM) of the engine, preferably to only allow an idle speed, if a lack of lubricant is  
4 at hand in the fuel.

1 Claim 4 (currently amended): A system according to ~~anyone of the above claims~~ claims 1 or 2,  
2 characterized in that said additive is an additive that changes, preferably increases, an electric  
3 conductivity or capacitance of a mixture of fuel and lubricant whereas said detector (16) is designed to  
4 detect the presence of the given additive in the lubricant mixed fuel in terms of electric conductivity or  
5 capacitance and whereas said threshold value is a threshold value for conductivity or capacitance.

1 Claim 5 (original): A system according to claim 4, characterized in that said detector (16) comprises two  
2 electrodes for the measurement of conductivity and capacitance

1 Claim 6 (currently amended): A system according to ~~any of the above claims~~ claim 1, characterized in  
2 that said additive[[,]] is an additive that changes an optical property in the mixture of fuel and lubricant,  
3 whereas said detector (16) is designed to detect the presence of a given additive in the lubricant mixed  
4 fuel in terms of this optical property and whereas said threshold value is a threshold value in terms of this  
5 optical property.

1 Claim 7 (original): A system in accordance to claim 6, characterized in that said detector comprises an  
2 optical sensor, preferably in the form of a light emitting diode (18) and a phototransistor (20) whereas  
3 the said additive is a colorant adapted to absorb light in the wavelength or spectrum of the light emitting  
4 diode.

1 Claim 8 (original): A method relating to the operation of an internal combustion engine (10) that is  
2 powered by a fuel mixed with a lubricant, characterized in that;  
3       •       a presence of a given additive in the lubricant mixed fuel is detected (16)

4           •       The detected presence of the additive is compared (24) with a set threshold value,  
5                   whereas it, when the lubricant is not mixed in the fuel or has been mixed into the fuel  
6                   in an amount lower than one through the additive against the threshold value correlated  
7                   amount, indicates (30) that a lack of lubricant is at hand in the fuel and/or whereas the  
8                   internal combustion engine operation is prevented or changed if said lack of lubricant  
9                   is at hand in the fuel.

1   Claim 9 (original): A method according to claim 8, characterized in that said threshold value is  
2   adjustable for correlation against the type of additive, and the limits for a mixing ratio between the fuel,  
3   lubricant and additive.

1   Claim 10 (original): A method according to claim 8 or 9, characterized in that the RPM of the engine  
2   (10) is limited (26) preferably that only the idle speed is allowed, if a lack of lubricant is at hand in the  
3   fuel.

1   Claim 11 (currently amended): A method according to ~~any of the claims 8-10~~ claim 8, characterized in  
2   that said additive is an additive that modifies, preferably increases, an electric conductivity or capacitance  
3   of the mixture of fuel and lubricant whereas the detection (16) of the presence of said additive in the  
4   lubricant mixed fuel is measured in terms of electrical conductivity or capacitance and whereas said  
5   threshold value is a threshold value in terms of electrical conductivity or capacitance.

1   Claim 12 (currently amended): A method according to ~~any of the claims 8-11~~ claim 8, characterized in  
2   that said additive is an additive that changes an optical property of a mixture of fuel and lubricant,  
3   whereas the detection (16) of the presence of the said additive in the lubricant mixed fuel is measured

Appl. No. N/A  
Amdt. Dated October 7, 2004  
Preliminary Amendment to National Phase Application  
in United States of PCT/SE03/00563

- 4 in terms of this optical property and whereas said threshold value is a threshold value in terms of this
- 5 optical property.